


# Lightology

lightology.com  
866-954-4489  
04-25-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **EDG1440090**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Flex Neon UDF7 Outdoor TruColor RGBTW Up/Down Bend 24V

By PureEdge Lighting



### Description

Flex Neon LRUDR8 TruColor RGBTW bends left and right or up and down with a 0.80 round lens that can be surface or flush mounted. Flex Neon offers superior color quality and performance while creating uniform illumination without pixelation. Sold as 5W5: 5 watts RGB and 5 watts Tunable White up to 20 feet; or 5W7: 5 watts RGB and 7 watts Tunable White up to 12 feet. Features E (end power input wire), CA (cap at end, no feed through), and W (outdoor wet location barrel connector cable leads) with an IP67 rating for outdoor wet locations. Pure Smart TruColor technology uses five channels of tunable LEDs, composed of RGBTW red, blue, green, and Tunable White (1500K-6500K), giving customers access to the warm glow of the sunset (1500K-2400K golden hour) to the pure white light of the mid-day sun (5700K) and everything in between. Flex Neon is offered with both indoor and wet-rated junction boxes (sold separately), which include a Pure Smart/WiZ Pro Bridgebox allowing for 5-Channel, full color, wireless control of the TruColor RGBTW Light Engine with the WiZ Pro Software Suite or Pure Smart Wi-Fi Room Controller (sold separately). System includes Outdoor 24VDC LED Flex Neon, End Cap, Power Connector (connected to each end of fixture), Wet Location Barrel Connectors, and Mounting Clips (provided with every two feet of Flex Neon). Note: System requires outdoor rated 24VDC RBGTW (PSBR) power supply, sold separately. Optional mounting accessories sold separately. Product is built to order.

### Specifications


COLOR	White
BODY FINISH	N/A
WATTAGE	25W
DIMMER	N/A
DIMENSIONS	60"L x 0.7"W x 0.5"H
INTEGRATED LED MODULE	5 x LED/5W/24V LED

### Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	96 CRI
LAMP COLOR	RGB+White
LUMENS/WATT	202.00
LUMINOUS FLUX	1010 lumens



Shown in white



CLICK TO VIEW PRODUCT

Notes: