



DESIGNER Gregory Kay
BRAND PureEdge Lighting




DESCRIPTION

Kurve Display Sign Light features a lambertian white diffuser that provides uniform light without hotspots and a special Feed Thru Stem for floating signs. At 7.5 watts per foot, the 24 volt DC channel fixture is available in 12 inch increments up to 120 inches. Available in a variety of color temperature in Satin Nickel or Black finish in 12 inch increments up to 120 inches. Arm extends 14 inches from wall. Hinges on the fixture arm rotates up to 90 degrees (from facing the wall to straight down). Can be powered using a 60 watt electronic low voltage (ELV) power supply (PS-60L-ELV) that fits inside junction box, or a Universal (UNI) power supply that requires a remote installation, sold separately. Universal power supply dimmable with electronic low voltage (ELV), Triac or 0-10V dimmer, sold separately. ETL listed. Major components made and assembled in the USA. Fixture includes a 5 year warranty. Product is built to order. Note: Required power supply and dimmer control sold separately.



Shown in: Satin Nickel

SHADE COLOR	N/A
BODY FINISH	Satin Nickel
WATTAGE	7.5W
DIMMER	Low Voltage Electronic
DIMENSIONS	12"L x 1.5"W x 1.4"H x 14"D
INTEGRATED LED MODULE	
LAMP	1 x LED/7.5W/24V LED
Technical Information	
LUMINOUS FLUX	270 lumens
LUMENS/WATT	36.00
LAMP COLOR	2700K
COLOR RENDERING	95 CRI
SPEC #	EDG145995



Feed-Through Power Stem

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE