

Lightology

lightology.com
866-954-4489
05-14-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **EDG146352**
Approved On: _____ Approved By: _____

Angle Display Sign 2.8 Square Canopy By PureEdge Lighting



Description


Angle Display Sign Light with 2.8 Inch Square Canopy features a lambertian white diffuser that provides uniform light without hotspots. At 7.5 watts per foot, the 24 volt DC channel is available in a variety of color temperature and finish options in 12 inch increments up to 120 inches. Arm extends 14 inches from wall. Hinges on the fixture arm rotates up to 90 degrees. Can be powered using a 60 watt electronic low voltage (ELV) power supply (PS-60L-ELV) that fits inside junction box, or a Universal (UNI) power supply that requires a remote installation, sold separately. Universal power supply dimmable with electronic low voltage (ELV), Triac or 0-10V dimmer, sold separately. Required power supply and dimmer control sold separately. Note: For indoor use only. Product is built to order. Note: Limited quantities available in White and Satin Aluminum finishes.

Specifications

COLOR N/A
BODY FINISH Satin Nickel
WATTAGE 7.5W
DIMMER Dimmable
DIMENSIONS 12"L x 1.37"W x 1.4"H x 14"D
INTEGRATED LED MODULE 1 x LED/7.5W/24V LED

Technical Information

LAMP LIFE 50000 hours
COLOR RENDERING 95 CRI
LAMP COLOR 2700K
LUMENS/WATT 36.00
LUMINOUS FLUX 270 lumens



Notes: