

Lightology

lightology.com
866-954-4489
04-28-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **EDG1464527**

Approved On: _____ Approved By: _____

48 Volt Universal DC LED Power Supply By PureEdge Lighting



Description

The PSB-96W-UNV-48VDC LED Class 2 power supply accepts input voltage of 120-277VAC and outputs 48VDC power up to 96 or 2x96 watts. Available in a standard remote or in-wall option. The solid state constant voltage Uni-power supply is compatible with most commercially available dimmers: Triac (forward phase) used for dimming of incandescent and low voltage magnetic transformers; ELV (reverse phase) - used for dimming electronic low voltage transformers; or 0-10V - dims the low voltage side of a 0-10V power supply commonly used in large scale lighting or commercial applications. Auto-reset, short circuit, and overload and thermal protection. Available in a remote, in-wall, and T-bar mount option. NOTE: Designed for use with PureEdge MicroTrack 48V Ceiling and Recessed Track.



Shown in white

Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	96W
DIMMER	Low Voltage Electronic
DIMENSIONS	9.25"W x 2"H x 3.5"D
BULB NOT INCLUDED	N/A



CLICK TO VIEW PRODUCT

Notes: