

Lightology

lightology.com
866-954-4489
02-12-26

Project:

Company:

Location:

Fixture Type:

SPEC #: EDG1530740

Approved On:

Approved By:

Verge Wall Warm Dim Plaster-In System By PureEdge Lighting



Description

Verge Wall Warm Dim is a slim, plaster-in aluminum channel with 4 inch paintable aluminum backer plate. Verge Wall creates and highlights the transition space where two drywall surfaces join together while emitting ambient illumination. Verge Warm Dim Wall is sold in 5 foot increments up to 40 feet and may be field cut to any length. Available in Warm Dim 27D (2700-1800K) or 30D (3000-1800K) color temperature. Verge requires a Universal (UNI) power supply, sold separately. UNI power supply compatible with TRIAC, ELV and 0-10V dimming. Required power supply, dimmer control, and optional accessories sold separately. Product is built to order. Included Components: Junction Box, Adjustable Mounting Bars, Backer Plate, Verge Wall Channel(s), Drywall Screws, LED Strip, and Lens(es)

Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	25W
DIMMER	Low Voltage Electronic
DIMENSIONS	60" L x 1.75" W x 4" H
INTEGRATED LED MODULE	5 x LED/5W/24V LED

Technical Information


LAMP LIFE	50000 hours
COLOR RENDERING	94 CRI
LAMP COLOR	2700K Warm Dim
LUMENS/WATT	199.00
LUMINOUS FLUX	995 lumens



Shown in white



INCLUDED COMPONENTS



- A. JUNCTION BOX: Junction box with Adjustable Mounting Bars. Low Voltage 24VDC wires from Remote Power Supply connect to the wires inside box. Junction box is designed to be surface mounted and recessed at the beginning of each run.
- B. ADJUSTABLE MOUNTING BARS: Provide flexibility for mounting in a variety of spaces.
- C. BACKER PLATE: Paintable aluminum plate that conceals Junction Box and reflects light.
- D. VERGE CHANNEL: 1.75" wide channel that houses a single row of LED Strip.
- E. DRYWALL SCREWS: Drywall screws for backer plate and backer.
- F. LED STRIP: Comes in Standard White or Dynamic Color Changing LED Strip. See lamp data sheet for additional details.
- G. LENS: 0.6" wide diffused lens projects a clean line of light without LED protrusion.



CLICK TO VIEW PRODUCT

Notes: