Lightology

lightology.com
866-954-4489
10-29-26

Project:

Company:

Location: Fixture Type:

SPEC #: **EDG1543538**

Approved On: Approved By:

TruCirque .5A Static White/Warm Dim Plaster-In LED System


By PureEdge Lighting


Description

The TruCirque .5A is an innovative and highly efficient that system blends seamlessly into the drywall, becoming part of the architecture and redefining the relationship between lighting and interior design. TruCirque brings the same ease of installation as other PureEdge 5/8 inch drywall families to a pristine circle of illumination. The slim extrusions are offered in various diameters from 2 to 18 feet, supplied with a diffused, flexible lens. TruCirque provides smooth, glare free illumination using high color rendering LEDs (CRI) offered in 2 watt (2.5 watts) 5 watt (5 watts) and 7 watt (7.5 watts) per foot options and Static White color temperature including Warm Dim 27D (2700K-1800K) and 30D (3000K-1800K). Note: Warm Dim available in 5 watt option only. Included Components: TruCirque .5 Inch Channel, Power Channel Connector(s) with Junction Box, Channel Joiners, Mounting Straps, Drywall Screws, LED Strip, and Flexible Diffused LensTruCirque requires a remote Universal (UNI) power supply (dimmable TRIAC/ELV/0-10V). Power supply and optional accessories sold separately.Maximum Diameter Before Re-Feeding:2WDC, 2.5 watts per foot -- 12 Feet5WDC, 5 watts per foot -- 6 Feet7WDC, 7.5 watts per foot -- 3 Feet



Shown in white





Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	4W
DIMMER	Low Voltage Electronic
DIMENSIONS	24"L x 0.5"W x 0.63"H
INTEGRATED LED MODULE	2 x LED/2W/24V LED

Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	92 CRI
LAMP COLOR	2700K
LUMENS/WATT	173.00
LUMINOUS FLUX	346 lumens

CLICK TO VIEW PRODUCT

Notes: