



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting

DESCRIPTION

Aurora Dual Halogen 3.3 Inch Round Edge Trimless Downlight with Housing is a specification grade, adjustable accent fixture for plaster or drywall construction. Two 12 volt MR16 37 watt IR maximum, or two MR16 LED 12 volt 7 watt bulbs, one per socket, are required, but not included. The flush mounted rigid plaster plate, which is finished into the ceiling, maintains a flat finish and defines the Truly Trimless Pure edge (knife edge) 3.3 inch aperture. Combined with the Aurora dome and the tilt gear hidden behind the lamp creates a clean internal lock. Features hot aiming with Philips screwdriver offering 20 to 45 degree vertical adjustment and 362 degree horizontal rotation without beam clipping. Includes standard 120 volt magnetic transformer, IC and air-tight, suitable for remodel or new construction. Secondary output voltage is 11.8 volts. Designed to accommodate ceiling thickness from .50 to 1.25 inches. Dome features anodized soft haze finish and hides electrical hardware, tilting for easy access to junction box and transformer. Includes two snoots and soft focus lenses, with room for two bulbs and two additional accessories. Aurora Gear Cover and light control accessories sold separately.



Shown in: White/ Haze Dome

TRIM COLOR	N/A
BODY FINISH	White/ Haze Dome
LAMP	2 x MR16/GU5.3 (bipin)/37W/12V Halogen 1 x MR16/GU5.3 (bipin)/7W/12V LED
WATTAGE	37W
DIMMER	Low Voltage Magnetic
DIMENSIONS	16.75"L x 14.5"W x 9.25"H



Technical Information

FUNCTION	Downlight
CEILING TYPE	Drywall Trimless/Flush
HOUSING TYPE	New construction IC Airtight
HOUSING HEIGHT	9"
APERTURE SHAPE	Round

ITEM NUMBER EDG155750



3.3 aperture
Truly Trimless



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE
