



lightology.com
866-954-4489
08-18-25

Project: _____	
Company: _____	
Location: _____	Fixture Type: _____
SPEC #: EDG160116	
Approved On: _____	Approved By: _____

RGB LED 700mA Constant Current Driver / Controller

By PureEdge Lighting

Description


RGB LED 700mA Constant Current Driver/ Controller is an easy to configure direct current controlled driver/controller for low power LED lighting applications. Can be integrated in a network or used as a standalone device. Control lighting with an external DMX Controller. Controller allows a show sequence for use in standalone mode. DMX, DALI and 0-10V dimming and color control. 3-button user interface with LCD display. The easy to navigate menu allows you to set parameters such as the number of channels or DMX or DALI settings for network mode and show, color, dim values for stand alone operation. Lock the driver's configuration and perform a test run of the connected LED groups. Power Input: 120-277VAC 50/60Hz. Power Output: 100W Maximum, 60V Max, 57 typical. Current range configurable from 200mA to 1,050mA (700mA with Edge Sun3 RGB). Indoor applications only. 12.14 inch width x 6.48 inch depth x 2.18 inch height. Compatible controllers include a CTP Touch Screen Controller or CDP Color Dial Controller, sold separately.

Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	100W
DIMMER	N/A
DIMENSIONS	12.14"W x 2.18"H x 6.48"D
BULB NOT INCLUDED	LED/100W/12V LED



Shown in white



CLICK TO VIEW PRODUCT

Notes: