



BRAND Priori

DESCRIPTION

3.5 Inch Line Voltage MR16 Airtight IC New Construction housing for areas with insulation. Insulation should be 3 inch minimum away from housing. Internal thermal protection. Adjustable mounting bars 10 to 24 inches. Requires one 50 watt maximum 120 volt GU10 MR16 halogen lamp, not included. Can also be used with one 2 watt 120 volt GU10 MR16 LED lamp, not included. cUL listed. For use with trims X3501, X3502, X3503, X3504, X3505, X3507 and X3508. Dimensions: 14.5 inch length x 13.4 inch width x 7.5 inch height. 3.622 inch ceiling cut out.



TRIM COLOR	N/A
BODY FINISH	Galvanized Steel
WATTAGE	50W
DIMMER	Standard 120V
DIMENSIONS	14.5"L x 13.4"W x 7.5"H
BULB NOT INCLUDED	
LAMP	1 x MR16/GU10/50W/120V Halogen 1 x MR16/GU10/2W/120V LED
Technical Information	
HOUSING TYPE	New construction IC
HOUSING HEIGHT	8"
APERTURE SHAPE	Round
SPEC #	PRI175973

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE