

lightology.com 866-954-4489 07-28-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG203630	
Approved On:	Approved By:

Verge Wall 2.5W Plaster-In System By PureEdge Lighting





Description

Verge Wall is a slim plaster-in aluminum channel with a 4 inch paintable aluminum backer plate. The channel highlights the transition where two drywall surfaces verge together, while emitting ambient illumination. Mounts directly to studs without joist modification and plasters into 5/8 inch or thicker drywall. Verge houses a single row of commercial grade LEDs available in a spectrum of color temperatures. Consumes 2.5 LED watts per foot and is sold in 5 foot increments up to 40 feet. Verge may be field-cut to any length. May be powered using a Universal (UNI) power supply with TRIAC/ELV dimming. For indoor applications only. Included components: Junction Box, Adjustable Mounting Bars, Verge Wall Channel(s), Backer Plate, Drywall Screws, LED Soft Strip, and Lens(es). A VG-1RE-JBOX rough-in junction box is available to rough-in electrical before drywall installation (included and sold separately). ETL listed. Suitable for damp locations. 5 year pro-rated warranty. Required power supply, dimmer control, and optional mounting accessories sold separately. Product is built to order. Note: Limited quantities available.

Specifications


COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE

Technical Information

LAMP LIFE .														500	000	hou	irs
COLOR RENDE	RING														:	95 C	RI
LAMP COLOR															:	2700	ΣK
LUMENS/WATT	г.,														:	372.0	00
LUMINOUS FLU	JX .													. 93	60 Iu	ımeı	ns



Shown in aluminum





CLICK TO VIEW PRODUCT

Notes:					
--------	--	--	--	--	--