

lightology.com 866-954-4489 09-14-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG203630	
Approved On:	Approved By:
Approved On.	дррголец Бу.

Verge Wall 2.5W Plaster-In System By PureEdge Lighting





Description

Verge Wall is a slim plaster-in aluminum channel with a 4 inch paintable aluminum backer plate. The channel highlights the transition where two drywall surfaces verge together, while emitting ambient illumination. Mounts directly to studs without joist modification and plasters into 5/8 inch or thicker drywall. Verge houses a single row of commercial grade LEDs available in a spectrum of color temperatures. Consumes 2.5 LED watts per foot and is sold in 5 foot increments up to 40 feet. Verge may be field-cut to any length. May be powered using a Universal (UNI) power supply with TRIAC/ELV dimming. For indoor applications only. Included components: Junction Box, Adjustable Mounting Bars, Verge Wall Channel(s), Backer Plate, Drywall Screws, LED Soft Strip, and Lens(es). A VG-1RE-JBOX rough-in junction box is available to rough-in electrical before drywall installation (included and sold separately). ETL listed. Suitable for damp locations. 5 year pro-rated warranty. Required power supply, dimmer control, and optional mounting accessories sold separately. Product is built to order. Note: Limited quantities available.

Specifications


COLOR		 N/A
BODY FINISH		 Aluminum
WATTAGE		 12.5W
DIMMER		 Low Voltage Electronic
DIMENSIONS		 60"L x 0.62"W x 4"H
INTEGRATED LED MO	DDULE	 5 x LED/2.5W/24V LED

Technical Information

LAMP LIFE	 										50000 hours
COLOR RENDERING	 										95 CRI
LAMP COLOR	 										2700K
LUMENS/WATT	 										372.00
LUMINOUS FLUX .	 		 								. 930 lumens



Shown in aluminum





CLICK TO VIEW PRODUCT

Notes:			