



BRANDWAC Lighting

DESCRIPTION

Tesla Spot 1 Light LED Non-IC AirTight New Construction Housing is made of 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel. Includes seven knockouts and four Romex style wiring connectors provided for ease of installation. Rated for branch wiring. Driver: Universal Input 120V-277V. Light Source: High output LED included with housing. Dimmable to 10 percent with low voltage electronic dimmer for 120 volt only or 0-10V dimming for 120 and 277 volt. Supplied with hanger bars, adjustable from 14.5 to 25 inches to accommodate various joist construction and grid sizes. Includes butterfly brackets which mount to .5 inch EMT or channel and are vertically adjustable. ETL listed. 6 1/8 x 6 1/8 inch cut out for trim version. 7.75 x 7.75 inch cut out for trimless version. Housing: 16.75 inch width x 12.25 inch depth x 5 inch height. For use with Tesla 1-Light LED Spot trims MT-5LD125, sold separately.



TRIM COLOR	N/A
BODY FINISH	N/A
WATTAGE	22.5W
DIMMER	Dimmable
DIMENSIONS	16.75"W x 5"H x 12.25"D
INTEGRATED LED MODULE	
LAMP	1 x LED/120V LED
Technical Information	
CEILING TYPE	Drywall with Trim
HOUSING TYPE	New construction NON IC Airtight
HOUSING HEIGHT	5"
SPEC #	WAC228287

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE