



BRAND

Contrast Lighting

DESCRIPTION



Concerto LED 4 Inch Low Profile Square Adjustable Trim features a Narrow Flood 47 degree beam angle in Warm White 3000K color temperature, 90CRI. For use with Concerto 1500 Lumen Performance 1 housing with 70 lumens per watt for a total of 1100 lumens, or 2000 Lumen Performance 2 housing with 68 lumens per watt for a total of 1575 lumens. Available in a 27 and 47 degree beam angle option. Provides high quality true color and a clean white light without hot spots. 360 degree swivel and 30 degree recliner adjustability with locking position. Includes Clear glass protection lens. Available in Matte White or Architectural Bronze powder coat finish, or Brushed Nickel plated die-formed steel finish. Available in other finishes upon request. Includes Bridgelux Vero 18 LED, delivering a lumen maintenance greater than 70 percent after 50,000 hours of operation. Ceiling cutout: 4.25 inch. UL listed for damp locations. See housing for dimming options. 5 year warranty on Concerto LED module. 1 year warranty on finish. Dimensions: 4.25 inch square outside dimension x 3.75 inch height. A complete fixture consists of a trim and housing, sold separately.



TRIM COLOR	Clear
BODY FINISH	Brushed Nickel
WATTAGE	16W
DIMMER	Dimmable
DIMENSIONS	4.9"W x 3.75"H x 4.9"D
INTEGRATED LED MODULE	
LAMP	1 x LED/16W/120V LED
	1 x LED/23W/120V LED

Technical Information

LUMINOUS FLUX	1575 lumens
LUMENS/WATT	98.44
LAMP COLOR	3000K
COLOR RENDERING	90 CRI
BEAM ANGLE	47°
LAMP LIFE	50000 hours
FUNCTION	Adjustable Accent
CEILING TYPE	Drywall with Trim
APERTURE SHAPE	Square
SPEC #	CLT233516



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE