



BRAND

Contrast Lighting

DESCRIPTION



Concerto LED 4 Inch Round Low Profile Adjustable Regressed Trim features a Narrow Flood 27 degree beam angle in Warm White 3000K color temperature, 90CRI. For use with Concerto 1500 Lumen Performance 1 housing with 69 lumens per watt for a total of 1070 lumens, or 2000 Lumen Performance 2 housing with 65 lumens per watt for a total of 1485 lumens. Available in a 27 and 48 degree beam angle option. Provides high quality true color and a clean white light without hot spots. Available in Brushed Nickel plated die-formed steel finish with Specular Clear, Natural Anodized, or Painted Black reflector, Matte White powder coat finish with Matte White, Specular Clear, Natural Anodized, or Painted Black reflector, or Architectural Bronze powder coat finish with Bronze, Specular Clear, Natural Anodized, or Painted Black reflector. Available in other finish combinations upon request. Includes Clear glass protective lens. Includes Bridgelux Vero 18 LED, delivering a lumen maintenance greater than 70 percent after 50,000 hours of operation. Ceiling cutout: 4.25 inch. UL listed for damp locations. See housing for dimming options. 5 year warranty on Concerto LED module. 1 year warranty on finish. Dimensions: 4.9 inch outside diameter x 4.5 inch height. A complete fixture consists of a trim and housing, sold separately.



TRIM COLOR	Clear
BODY FINISH	Brushed Nickel/ Anodized Reflector
WATTAGE	16W
DIMMER	Dimmable
DIMENSIONS	4.9"W x 4.5"H
INTEGRATED LED MODULE	
LAMP	1 x LED/16W/120V LED 1 x LED/23W/120V LED

Technical Information

LUMINOUS FLUX	1485 lumens
LUMENS/WATT	92.81
LAMP COLOR	3000K
COLOR RENDERING	90 CRI
BEAM ANGLE	27°
LAMP LIFE	50000 hours
FUNCTION	Adjustable Accent
CEILING TYPE	Drywall with Trim
APERTURE SHAPE	Round
SPEC #	CLT233583



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE
