



**BRAND**

Contrast Lighting

**DESCRIPTION**

Concerto LED 4 Inch Round Low Profile Adjustable Regressed Trim features a Flood 48 degree beam angle in Warm White 3000K color temperature, 90CRI. For use with Concerto 16 Watt 1500 Lumen Performance 1 housing with 69 lumens per watt for a total of 1070 lumens, or 23 Watt 2000 Lumen Performance 2 housing with 65 lumens per watt for a total of 1485 lumens. Available in a 27 and 48 degree beam angle option. Provides high quality true color and a clean white light without hot spots. Available in Brushed Nickel plated die-formed steel finish with Specular Clear, Natural Anodized, or Painted Black reflector, Matte White powder coat finish with Matte White, Specular Clear, Natural Anodized, or Painted Black reflector, or Architectural Bronze powder coat finish with Bronze, Specular Clear, Natural Anodized, or Painted Black reflector. Available in other finish combinations upon request. Includes Clear glass protective lens. Includes Bridgelux Vero 18 LED, delivering a lumen maintenance greater than 70 percent after 50,000 hours of operation. Ceiling cutout: 4.25 inch. UL listed for damp locations. See housing for dimming options. 5 year warranty on Concerto LED module. 1 year warranty on finish. Dimensions: 4.9 inch outside diameter x 4.5 inch height. A complete fixture consists of a trim and housing, sold separately.




*Shown in: Brushed Nickel/ Anodized Reflector / Clear*

<b>TRIM COLOR</b>	Clear
<b>BODY FINISH</b>	Brushed Nickel/ Anodized Reflector
<b>LAMP</b>	1 x LED/16W/120V LED 1 x LED/23W/120V LED
<b>WATTAGE</b>	16W
<b>DIMMER</b>	Dimmable
<b>DIMENSIONS</b>	4.9"W x 4.5"H

*Technical Information*

<b>LUMINOUS FLUX</b>	1485 lumens
<b>LUMENS/WATT</b>	92.81
<b>LAMP COLOR</b>	3000 K
<b>COLOR RENDERING</b>	90 CRI
<b>BEAM ANGLE</b>	48°
<b>LAMP LIFE</b>	50000 hours
<b>FUNCTION</b>	Adjustable Accent
<b>CEILING TYPE</b>	Drywall with Trim
<b>APERTURE SHAPE</b>	Round

**PRODUCT NUMBER** CLT233584



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE

---