



### BRAND

Contrast Lighting

### DESCRIPTION



Concerto LED 4 Inch Square Low Profile Adjustable Regressed Trim features a Flood 48 degree beam angle in Warm White 3000K color temperature, 90CRI. For use with Concerto 1500 Lumen Performance 1 housing with 69 lumens per watt for a total of 1070 lumens, or 2000 Lumen Performance 2 housing with 65 lumens per watt for a total of 1485 lumens. Available in a 27 and 48 degree beam angle option. Provides high quality true color and a clean white light without hot spots. Available in other finish combinations upon request. Includes Clear glass protective lens. Includes Bridgelux Vero 18 LED, delivering a lumen maintenance greater than 70 percent after 50,000 hours of operation. Ceiling cutout: 4.25 inch. UL listed for damp locations. See housing for dimming options. 5 year warranty on Concerto LED module. 1 year warranty on finish. Dimensions: 4.9 inch square outside dimension x 4.5 inch height. A complete fixture consists of a trim and housing, sold separately.



TRIM COLOR	Clear
BODY FINISH	Brushed Nickel/ Specular Clear Reflector
WATTAGE	16W
DIMMER	Dimmable
DIMENSIONS	4.9"W x 4.5"H x 4.9"D
INTEGRATED LED MODULE	
LAMP	1 x LED/16W/120V LED 1 x LED/23W/120V LED

#### Technical Information

LUMINOUS FLUX	1485 lumens
LUMENS/WATT	92.81
LAMP COLOR	3000K
COLOR RENDERING	90 CRI
BEAM ANGLE	48°
LAMP LIFE	50000 hours
FUNCTION	Adjustable Accent
CEILING TYPE	Drywall with Trim
APERTURE SHAPE	Square
SPEC #	CLT233623



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE