



BRAND

Contrast Lighting

DESCRIPTION



Concerto LED 4 Inch Square Lensed Low Profile Shower Trim features a Flood 51 degree beam angle in Warm White 3000K color temperature, 90CRI. For use with Concerto 1500 Lumen Performance 1 housing with 55 lumens per watt for a total of 860 lumens, or 2000 Lumen Performance 2 housing with 53 lumens per watt for a total of 1206 lumens. Provides high quality true color and a clean white light without hot spots. Available in Matte White or Brushed Nickel plated die-formed steel finish. Available in other finishes upon request. Includes Bridgelux Vero 18 LED, delivering a lumen maintenance greater than 70 percent after 50,000 hours of operation. Tempered glass frosted lens. Ceiling cutout: 4.25 inch. UL listed for wet locations. See housing for dimming options. 5 year warranty on Concerto LED module. 1 year warranty on finish. Dimensions: 4.9 inch square outside dimension x 4.7 inch height. A complete fixture consists of a trim and housing, sold separately.



TRIM COLOR	Frosted
BODY FINISH	Architectural Bronze
WATTAGE	16W
DIMMER	Dimmable
DIMENSIONS	4.9"W x 4.7"H x 4.9"D
INTEGRATED LED MODULE	
LAMP	1 x LED/120V LED
	1 x LED/120V LED

Technical Information

LUMINOUS FLUX	1205 lumens
LUMENS/WATT	75.31
LAMP COLOR	3000K
COLOR RENDERING	90 CRI
BEAM ANGLE	51°
LAMP LIFE	50000 hours
FUNCTION	Shower/Wet Location
CEILING TYPE	Drywall with Trim
APERTURE SHAPE	Square
SPEC #	CLT233624



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE