



BRAND

Contrast Lighting

DESCRIPTION



Concerto LED 4 Inch Square Low Profile Regressed Trim features a Flood 48 degree beam angle in Warm White 3000K color temperature, 90CRI, 63 delivered lumens per watt for a total of 1850 lumens combined with a 2500 Lumen Performance 3 housing. Available in a 33 and 48 degree beam angle option. Provides high quality true color and a clean white light without hot spots. Available in Brushed Nickel plated die-formed steel finish with Specular Clear, Specular Black, Natural Anodized, or Painted Black reflector, Matte White powder coat finish with Matte White, Specular Clear, Natural Anodized, Specular Black, or Painted Black reflector, or Architectural Bronze powder coat finish with Bronze, Specular Clear, Natural Anodized, Specular Black or Painted Black reflector. Available in other finish combinations upon request. Includes Clear glass protective lens. Includes Cree CXA2530 30 Watt LED, delivering a lumen maintenance greater than 70 percent after 50,000 hours of operation. Ceiling cutout: 4.25 inch. UL listed for damp locations. See housing for dimming options. 5 year warranty on Concerto LED module. 1 year warranty on finish. Dimensions: 4.9 inch square outside dimension x 4.3 inch height. A complete fixture consists of a trim and housing, sold separately.



TRIM COLOR	Clear
BODY FINISH	Brushed Nickel/ Anodized Reflector
WATTAGE	30W
DIMMER	Dimmable
DIMENSIONS	4.9"W x 4.3"H x 4.9"D
INTEGRATED LED MODULE	
LAMP	1 x LED/30W/120V LED

Technical Information

LUMINOUS FLUX	1850 lumens
LUMENS/WATT	61.67
LAMP COLOR	3000K
COLOR RENDERING	90 CRI
BEAM ANGLE	48°
LAMP LIFE	50000 hours
FUNCTION	Downlight
CEILING TYPE	Drywall with Trim
APERTURE SHAPE	Square
SPEC #	CLT233866



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE