

Concerto 4 2000 Lumen 0-10 Dimmable IC Housing

SPEC # CLT234259







BRAND


Contrast Lighting


DESCRIPTION

Concerto 4 Inch 0-10 Dim 2000 Lumen Performance 2 LED IC New Construction Housing is made of galvanized steel with a thickness up to 18 gauge. Below ceiling accessible. IC designation indicates that housing can be in direct contact with insulation, except polyurethane. Can fit in ceilings up to 1.5 inch thick. No light leakage. Mounting bars extend from 10 to 24.5 inches to fit in most ceiling structures. Ceiling cutout: 4.25 inch. Dimmable with a 0-10 volt dimmer per attached 4 Inch Concerto Performance 2 housings, 0-10 dimming outline. UL listed for damp and wet locations. 5 year warranty on LED driver. Dimensions: 19.5 inch width x 10 inch depth x 7.1 inch height. A complete fixture consists of a housing and trim, sold separately.



TRIM COLOR N/A **BODY FINISH** Galvanized Steel WATTAGE 23W DIMMER 0-10V DIMENSIONS 19.5"W x 7.1"H x 10"D INTEGRATED LED MODULE LAMP 1 x LED/23W/120V LED Technical Information LUMINOUS FLUX 2000 lumens LUMENS/WATT 86.96 CELLING TYPE Drywall with Trim HOUSING TYPE New construction IC





COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE

CLT234259

SPEC #