

Lightology

lightology.com
866-954-4489
07-05-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **SRA239794**
Approved On: _____ Approved By: _____

Vivid 3 LED MR16 GU5.3 7.5W 36 Deg 2700K 95CRI

By Soraa



Description

Vivid 3 7.5 Watt 12 volt LED GU5.3 base MR16 from Soraa with 10, 25 or 36 degree beam angle in Very Warm White 2700K, Warm White 3000K, or Neutral White 4000K, 95CRI. Lumen output range of 390 to 455 lumens. Equivalent to a 50 watt halogen. 35,000 hour average lamp life. Saves over 85 percent of energy compared to standard halogen lamps. LED retrofit lamp to replace 12 volt MR16 GU5.3 base halogen lamps in recessed downlights, track lighting, and other indoor and outdoor applications. Dimmable to less than 20 percent with trailing edge and leading edge phase cut dimmers, 12 volt AC magnetic and electronic transformers and 12 volt DC transformers (see attached manufacturer specification for dimmer and transformer compatibility). UL listed. Suitable for fully enclosed fixtures (subject to manufacturer maximum heatsink temperature limits) and damp locations. 3 year warranty or 25,000 hours (whichever comes first). 10 Degree beam angle version SNAP accessory compatible, sold separately.

Specifications


COLOR Silver
BODY FINISH N/A
WATTAGE 7.5W
DIMMER Dimmable
DIMENSIONS 1.97"W x 1.79"H
BULB 1 x MR16/GU5.3 (bipin)/7.5W/12V LED

Technical Information

LAMP LIFE 35000 hours
BEAM ANGLE 36°
COLOR RENDERING 95 CRI
LAMP COLOR 2700K
LUMENS/WATT 54.67
LUMINOUS FLUX 410 lumens



Shown in silver



CLICK TO VIEW PRODUCT

Notes: