

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: JUN25876	
Approved On:	Approved By:

IC20R 5 Inch IC Remodel Housing By Juno Lighting









Description

IC20R 5 Inch IC Remodel Housing is an energy efficient sealed housing. IC remodel housing for remodel application where back side of ceiling is not accessible. Installs through an opening in the ceiling from below. Secured in place by factory installed remodel springs. Can be completely covered with insulation. When used with Air-Loc gasket (ALGSR), stops infiltration and exfiltration of air, reducing heating and cooling costs. Trims shown with Air-Loc symbol do not require a gasket. One 120 volt, A19, BR30, PAR30, PAR20, R20, PAR30L or A15 medium base lamp or LED equivalent is required, but not included. Lamp type and wattage dependent upon housing/trim combination (see attached Juno manufacturer specification). Incandescent/halogen dimmable with a standard incandescent dimmer. Consult lamp manufacturer for dimmer compatibility when using an LED equivalent lamp. UL listed for through-branch wiring, damp locations and IP. Product thermally protected against improper use of lamps. Trims 210N, 211 and 212N are wet location approved for covered ceiling applications. Trims 215 and 216 are wet location approved for covered ceiling applications when used with outdoor rated lamps. 12.5 inch length x 5.9 inch width x 7.5 inch height. A complete fixture includes a housing and trim, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR
BODY FINISH
WATTAGE
DIMMER Dimmable
DIMENSIONS
BULB NOT INCLUDED 1 x A19/Medium (E26)/120V Incandescent
OTHER BULB OPTIONS 1 x A19/Medium (E26)/120V LED
1 x A15/Medium (E26)/120V Incandescent
1 x A15/Medium (E26)/120V LED
1 x BR30/Medium (E26)/120V Halogen
1 x BR30/Medium (E26)/120V Incandescent
1 x BR30/Medium (E26)/120V LED
1 x PAR30L/Medium (E26)/120V Haloger
1 x PAR30L/Medium (E26)/120V LED
1 x PAR30S/Medium (E26)/120V Haloger
1 x PAR30S/Medium (E26)/120V LED
1 x R20/Medium (E26)/120V Incandescent
1 x R20/Medium (E26)/120V LED
1 x PAR20/Medium (E26)/120V Haloger
1 x PAR20/Medium (E26)/120V LED



Cutout: 5.50 inch	 								ŝ.	N:	SIC	NS	MEI	T DI	ODUC	Ы
8"	 											ΗТ	IGH	G HE	USIN	Н
Remodel IC	 												ÞΕ	G TYF	USIN	Н
Drywall with Trim	 												Ξ.	TYPE	ILING	C



Shown in aluminum





CLICK TO VIEW PRODUCT

Notes:	