

lightology.com 866-954-4489 07-04-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: JUN25877	
Approved On:	Approved By:

IC21R 6 Inch IC Remodel Shallow Housing By Juno Lighting






Description

IC2IR 6 Inch IC Remodel Housing is an energy efficient sealed housing. IC remodel housing for remodel application where back side of ceiling is not accessible. Installs through an opening in the ceiling from below. Secured in place by factory installed remodel springs. Can be completely covered with insulation. When used with Air-Loc gasket (ALG6R), stops infiltration and ex-filtration of air, reducing heating and cooling costs. Trims shown with Air-Loc symbol do not require a gasket. One 120 volt, A19, BR30, PAR30, PAR30L, PAR20 or R20 medium base lamp or LED equivalent is required, but not included. Lamp type and wattage dependent upon housing/trim combination (see attached Juno manufacturer specification). Incandescent/halogen dimmable with a standard incandescent dimmer. Consult lamp manufacturer for dimmer compatibility when using an LED equivalent lamp. UL listed for through-branch wiring, damp locations and IP. Product thermally protected against improper use of lamps. Trim 241 is wet location approved for covered ceiling applications. 13.75 inch length x 7.3 inch width x 5.75 inch height. A complete fixture includes a housing and trim, sold separately.


Specifications



PRODUCT DIMENSIONS Cutout: 6.75 inch
HOUSING HEIGHT
HOUSING TYPE
CEILING TYPE



Shown in aluminum





6 3/4" CEILING CUTOUT



CLICK TO VIEW PRODUCT

Notes: