

lightology.com 866-954-4489 07-03-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: JUN25881	
Approved On:	Approved By:

IC23 6 Inch Economy New Construction IC Housing 120V By Juno Lighting





Description

IC23 6 Inch Economy IC New Construction Housing is an energy efficient aluminum housing. IC designation allows for housing to be completely covered with insulation. Accommodates ceiling thickness up to 1 inch. When used with Air-Loc gasket (ALG6), stops infiltration and exfiltration of air, reducing heating and cooling costs. Trims shown with Air-Loc symbol do not require a gasket. One 120 volt, A19, BR30, BR40, PAR30, PAR20, R20 or PAR38 medium base incandescent/halogen or LED equivalent lamp is required, but not included. Lamp type and wattage dependent on housing/trim combination. Halogen/incandescent dimmable with a standard incandescent dimmer. Consult lamp manufacturer for dimmer compatibility when using an LED equivalent. UL listed for through-branch wiring and damp locations. Trims 239 and 241 are wet location approved for covered ceiling applications. Trims 28 and 29 are wet location approved when used with outdoor rated lamps. 13.1 inch leight. A complete fixture includes a housing and trim, sold separately.

Specifications


•
REFLECTOR/BAFFLE COLOR
BODY FINISH
WATTAGE
DIMMER Dimmable
DIMENSIONS
BULB NOT INCLUDED 1 x PAR38/Medium (E26)/120V Halogen
OTHER BULB OPTIONS 1 x PAR38/Medium (E26)/120V LED
1 x A19/Medium (E26)/120V Incandescent
1 x A19/Medium (E26)/120V Incandescent
1 x A19/Medium (E26)/120V LED
1 x BR30/Medium (E26)/120V Halogen
1 x BR30/Medium (E26)/120V Incandescent
1 x BR30/Medium (E26)/120V LED
1 x BR40/Medium (E26)/120V Incandescent
1 x BR40/Medium (E26)/120V LED
1 x PAR30L/Medium (E26)/120V Halogen
1 x PAR30L/Medium (E26)/120V LED
1 x PAR30S/Medium (E26)/120V Halogen
1x PAR30S/Medium (E26)/120V LED
1 x R20/Medium (E26)/120V Incandescent
1 x R20/Medium (E26)/120V LED
1 x PAR20/Medium (E26)/120V Halogen
1 x PAR20/Medium (E26)/120V LED

Technical Information

Cutout: 6.88 inch									۱S	ЛC	SIC	IEN	CT DIM	RODUC	Ρ
8"											Γ.	3H°	G HEIC	OUSING	Н
New construction IC												Ē	G TYPE	OUSING	Н
Drywall with Trim													TYPE	EILING	С



Shown in aluminum





CLICK TO VIEW PRODUCT

Notes:		