

lightology.com 866-954-4489 07-05-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: <b>JUN25892</b>	
Approved On:	Approved By:

## IC928 6IN Super Slope Ceiling IC New Construction Housing By Juno Lighting





## Description

IC928 6 Inch Super Slope Ceiling IC New Construction Housing for use in slope ceiling applications with a 7/12 to 12/12 pitch (30 to 45 degrees). Designed for use in insulated areas which allows housing to be completely covered with insulation. Adjustable to position lamp perpendicular to floor. One 120 volt, PAR38, PAR30, BR30, or PAR16 medium base halogen/incandescent or LED equivalent lamp is required, but not included. Halogen and incandescent lamps dimmable using a standard incandescent dimmer. Consult lamp manufacturer for dimmer compatibility when using an LED equivalent lamp. Lamp type/wattage dependent upon housing/trim combination (see attached Juno manufacturer specification). UL listed for throughbranch wiring, damp locations and IP. Wet location approved for covered ceiling applications with trim 603. Air-Loc gasket (ALG928), sold separately, stops infiltration and exfiltration of air, reducing heating and cooling. 18.5 inch length x 9.1 inch width x 7.6 inch height. A complete fixture includes a housing and trim, sold separately.

## Specifications


REFLECTOR/BAFFLE COLOR
BODY FINISH
WATTAGE
DIMMER Dimmable
DIMENSIONS
BULB NOT INCLUDED 1 x PAR30/Medium (E26)/75W/120V Halogen
OTHER BULB OPTIONS 1 x BR30/Medium (E26)/120V Halogen
1 x BR30/Medium (E26)/120V Incandescent
1 x BR30/Medium (E26)/120V LED
1 x PAR16/Medium (E26)/120V Halogen
1 x PAR16/Medium (E26)/120V LED
1 x PAR30S/Medium (E26)/120V Halogen
1x PAR30S/Medium (E26)/120V LED
1 x PAR38/Medium (E26)/120V LED

## **Technical Information**

PRODUCT DIMENSIONS
HOUSING HEIGHT
HOUSING TYPE New Construction Slope IC
CEILING TYPE



Shown in aluminum





CLICK TO VIEW PRODUCT

Notes:	
--------	--