

Lightology

lightology.com
866-954-4489
06-04-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **JUN26401**

Approved On: _____ Approved By: _____

TC943N Aculux 3.25 Inch Non-IC New Construction Housing By Juno Lighting




Description

Aculux TC943N 3.25 Inch Non-IC New Construction Housing is designed for use in non-insulated areas or where insulation is spaced at least 3 inches away from housing. Features Acu-Aim precision geared hot-aiming with 370 degree rotation and 45 degree tilt. One MR16 GU5.3 base halogen lamp up to 75 watts (or LED equivalent) is required, but not included. Includes a magnetic low voltage transformer. Dimmable with a low voltage magnetic dimmer, sold separately. 14.5 inch width x 8.5 inch depth x 5.44 inch height. A complete fixture includes a housing and trim, sold separately.



Shown in aluminum



Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	75W
DIMMER	Low Voltage Magnetic
DIMENSIONS	14.5"W x 5.44"H x 8.5"D
BULB NOT INCLUDED	1 x MR16/GU5.3 (bipin)/75W/12V Halogen

Technical Information

APERTURE SIZE	3.250"
HOUSING HEIGHT	6"
HOUSING TYPE	New Construction NON IC
CEILING TYPE	Drywall with Trim



CLICK TO VIEW PRODUCT

Notes: