



lightology.com  
866-954-4489  
12-28-25

Project: _____	
Company: _____	
Location: _____	Fixture Type: _____
SPEC #: <b>JUN26401</b>	
Approved On: _____	Approved By: _____

## TC943N Aculux 3.25 Inch Non-IC New Construction Housing

By Juno Lighting



### Description

Aculux TC943N 3.25 Inch Non-IC New Construction Housing is designed for use in non-insulated areas or where insulation is spaced at least 3 inches away from housing. Features Acu-Aim precision geared hot-aiming with 370 degree rotation and 45 degree tilt. One MR16 GU5.3 base halogen lamp up to 75 watts (or LED equivalent) is required, but not included. Includes a magnetic low voltage transformer. Dimmable with a low voltage magnetic dimmer, sold separately. 14.5 inch width x 8.5 inch depth x 5.44 inch height. A complete fixture includes a housing and trim, sold separately.

### Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	75W
DIMMER	Low Voltage Magnetic
DIMENSIONS	14.5"W x 5.44"H x 8.5"D
BULB NOT INCLUDED	1 x MR16/GU5.3 (bipin)/75W/12V Halogen

### Technical Information

APERTURE SIZE	3.250"
HOUSING HEIGHT	6"
HOUSING TYPE	New Construction NON IC
CEILING TYPE	Drywall with Trim



Shown in aluminum



CLICK TO VIEW PRODUCT

Notes: