

# Lightology

lightology.com  
866-954-4489  
07-03-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG331247**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_


## Light Channel 1.6 Trim Recessed

By PureEdge Lighting



### Description

Light Channel Trim 1.6 provides a clean line of glare-free general illumination. Fixture recesses within the thickness of 5/8 inch drywall or wood (wall, ceiling or millwork). System mounts to studs without joist modification. Available with a thin border in a metal finish. The 24VDC linear 5 watt (2X2.5W) or 10 watt (2X5W) LED system houses two rows of high CRI commercial grade white LED Soft Strip in two wattages and a spectrum of color temperature options. System is ordered in 12 inch increments up to 120 inches. System can be powered with a 24VDC Universal (UNI) power supply (dimmable ELV/TRIAC/0-10V). Required power supply and dimmer control, sold separately. Product is built to order.



### Specifications

COLOR	N/A
BODY FINISH	Satin Nickel
WATTAGE	5W
DIMMER	Dimmable
DIMENSIONS	12\"L x 2.75\"W x 3.2\"H
INTEGRATED LED MODULE	1 x LED/5W/24V LED

### Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	85 CRI
LAMP COLOR	3500K
LUMENS/WATT	77.20
LUMINOUS FLUX	386 lumens

Notes: