

lightology.com 866-954-4489 11-05-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG331247	
Approved On:	Approved By:

Light Channel 1.6 Trim Recessed By PureEdge Lighting








Description

Light Channel Trim 1.6 provides a clean line of glare-free general illumination. Fixture recesses within the thickness of 5/8 inch drywall or wood (wall, ceiling or millwork). System mounts to studs without joist modification. Available with a thin border in a metal finish. The 24VDC linear 5 watt (2X2.5W) or 10 watt (2X5W) LED system houses two rows of high CRI commercial grade white LED Soft Strip in two wattages and a spectrum of color temperature options. System is ordered in 12 inch increments up to 120 inches. System can be powered with a 24VDC Universal (UNI) power supply (dimmable ELV/TRIAC/0-10V). Required power supply and dimmer control, sold separately. Product is built to order.



Specifications

COLOR
BODY FINISH
WATTAGE
DIMMER Dimmable
DIMENSIONS
INTEGRATED LED MODULE 1x LED/5W/24V LED

Technical Information

LAMP LIFE											50000 hours
COLOR RENDERING											85 CRI
LAMP COLOR											3500K
LUMENS/WATT											77.20
LUMINOUS FLUX .											. 386 lumens

Notes: