

# Lightology

lightology.com  
866-954-4489  
05-22-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **EDG340119**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Reveal Cove/Pathway RGB Plaster-In LED System 24V By PureEdge Lighting




### Description

Reveal RGB (Red-Blue-Green), a 24VDC linear LED system, features a shallow plaster-in aluminum extrusion. May be secured directly to studs without joist modification and plasters into .50 inch or thicker drywall, or between studs. Reveal is sold in 12 inch increments up to 20 feet (5 watt). May be field-cut to any length. Available in a variety of finishes. System includes Junction Box, Adjustable Mounting Bars, Reveal Channel(s), Power Feed End Cap, Junction Box Cover, Dead End Cap, Take-Up Box, Drywall Screws, and LED Soft Strip. Requires a remote RGB power supply with integrated RGB DMX driver. Required power supply, controller, and optional mounting accessories sold separately. Note: Product is built to order.



Shown in white



**INCLUDED COMPONENTS**

- A. JUNCTION BOX**  
Mounts behind drywall with Adjustable Mounting Bars, and includes a drywall template for accurate installation. Low Voltage 24VDC wires from Remote Power Supply connect to LED wires inside box. Junction Box opening is concealed with the Reveal Junction Box cover and is required at the beginning of each run.
- B. ADJUSTABLE MOUNTING BARS**  
Provides flexibility for mounting in a variety of spaces.
- C. REVEAL CHANNEL**  
2 1/2" deep extrusion houses a single row of commercial-grade White or Dynamic Color Changing LED Soft Strip.
- D. POWER FEED END CAP**  
Provides a connection area for 24VDC wires at beginning of run where LED Soft Strip enters channel.
- E. JUNCTION BOX COVER**  
Conceals Junction Box opening. Required at the beginning of each run.
- F. DEAD END CAP PLATE**  
Provides a finished look and prevents light leak at feed-end of run where LED Soft Strip enters channel.
- G. TAKE-UP BOX**  
Prevents slack at end of run by tucking excess LED Soft Strip safely behind wall.
- H. DRYWALL SCREWS**  
Secures channel to drywall and stud.
- I. LED SOFT STRIP**  
Back Side shows commercial-grade White or Dynamic Color Changing LED Soft Strip. See lamp data on for additional details.

### Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	5W
DIMMER	N/A
DIMENSIONS	12"L x 4.375"W x 0.75"D
INTEGRATED LED MODULE	1 x LED/5W/24V LED



CLICK TO VIEW PRODUCT

Notes: