



BRAND

PureEdge Lighting

DESCRIPTION

TruLine 1.6A, a versatile 24VDC linear plaster-in LED system, creates glare-free indoor architectural lighting. The 24VDC Plaster-In LED System recesses into 5/8 inch drywall without any joist modification. The slim extrusions, LED strips, and lenses are field-cutttable and can be ordered in 1 foot increments up to 20 feet. Includes 5 watts (2X2.5 watts) LED per foot with color temperature options in 2700K and 3000K. Can be run in vertical, horizontal and diagonal directions. Product is built to order. Included components: TruLine 1.6A channel(s), LED Soft Strip, TL1.6A Junction Box, Take-Up Box, Adjustable Mounting Bars, Mounting Strap, Power End Cap, Drywall Screw, and Lenses. System requires a 24 volt electronic low voltage (ELV) PS-60L-ELV-24VDC power supply (ELV dimming) which fits inside junction box or remote Universal (UNI) power supply (TRIAC/ELV/0-10V dimming), sold separately. Note: Required power supply, dimmer, and optional mounting components sold separately. Overstock is for a 40 foot section, 5 watts per foot (200 watts) in 4000K Cool White color temperature.



SHADE COLOR	N/A
BODY FINISH	White
WATTAGE	200W
DIMMER	Low Voltage Electronic
DIMENSIONS	480"L x 3.73"W x 0.63"D
INTEGRATED LED MODULE	
LAMP	1 x LED/200W/24V LED

Technical Information

LUMINOUS FLUX	15440 lumens
LUMENS/WATT	77.20
LAMP COLOR	4000K
COLOR RENDERING	85 CRI

SPEC # EDG340427

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE