

Lightology

lightology.com
866-954-4489
02-11-26

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **ELE342558**
Approved On: _____ Approved By: _____

Burk Freejack Head

By Visual Comfort Architectural



Description

Burk Freejack Head combines design simplicity inspired by a telephoto camera lens. Compatible for use with 1-circuit and 2-circuit Monorail track systems or Freejack canopy. Features 20 or 35 degree field changeable optics and integrated lens holder which accommodates up to two MR16 size lenses or louvers, sold separately. Includes 12 volt, 12 watt field replaceable LED module. Includes a Freejack connector. As a general rule when using the Burk head, it is not recommended using greater than 33 percent of the maximum wattage specified for the low voltage transformer due to in-rush current requirements. Freejack canopy required if used as a monopoint, sold separately. LED canopy compatible with both halogen and LED lamp options. Dimmer type dependent on system transformer (low voltage magnetic or electronic).

Specifications


COLOR	N/A
BODY FINISH	Black / Satin Nickel
WATTAGE	12W
DIMMER	Dimmable
DIMENSIONS	3"L x 3"W x 3.6"D
INTEGRATED LED MODULE	1 x LED/12W/12V LED
COUNTRY OF ORIGIN	China

Technical Information

LAMP LIFE	50000 hours
BEAM ANGLE	20°
COLOR RENDERING	80 CRI
LAMP COLOR	2700K
LUMENS/WATT	61.42
LUMINOUS FLUX	737 lumens



Shown in black / satin nickel



CLICK TO VIEW PRODUCT

Notes: