

lightology.com 866-954-4489 12-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG356939	
Approved On:	Approved By:

Verge Wall 5W 2K4K Variable White Plaster-In System By PureEdge Lighting








Description

Verge Wall 2K4K Variable White is a slim plaster-in aluminum channel with paintable aluminum backer plate which highlights the transition where two drywall surfaces verge together, while emitting ambient illumination. Verge houses a single row of commercial grade white LEDs available in Tunable White 2000-4000K color temperature. Consumes 5 LED watts per foot. Verge is sold in 5 foot increments up to 20 feet and may be field-cut to any length. The system requires a 24VDC electronic low voltage (ELV), 0-10V, or DMX remote power supply, controlled with a Tunable White (CDMX1) touch controller, sold separately. ETL listed. Suitable for damp locations. For indoor applications only. Fixture includes a 5 year pro-rated warranty. Included components: Junction Box, Adjustable Mounting Bars, Verge Wall Channel(s), Backer Plate, Drywall Screws, LED Soft Strip, and Lens(es). A VG-1RE-JBOX rough-in junction box is available to rough-in electrical before drywall installation (included and sold separately). Required power supply, dimmer control, and optional mounting accessories sold separately. Product is built to order.

Specifications

BODY FINISH
WATTAGE
DIMMER Dimmable
DIMENSIONS
INTEGRATED LED MODULE
Technical Information
COLOR RENDERING
LAMP COLOR
LUMENS/WATT
LLIMINIOLIS ELLIY 1930 lumens





Notes: