

Lightology

lightology.com
866-954-4489
05-12-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **ELE361056**

Approved On: _____ Approved By: _____

Element 3IN RD Flanged Downlight Remodel Housing

By Visual Comfort Architectural



Description

3IN RD Flanged Fixed Downlight Remodel Non-IC Housing for use with round flanged trims. Includes 17 or 12 watt LED module with Warm Dim LED (3000K-1800K) or choice of 2700K, 3000K or 3500K color temperature and 10, 18, 25, 40 or 60 degree beam angle. 3 7/8 inch ceiling opening. Suitable for damp locations. Suitable for wet locations with shower trim option. Includes a 120-277V Universal driver dimmable with standard reverse-phase, forward-phase, TRIAC, and 0-10V dimming. Note: A complete fixture requires a housing and trim, sold separately. Note: Warm Dim option is not available with 10 degree beam angle.

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	17W
DIMMER	Low Voltage Electronic
DIMENSIONS	3.8"W x 5"H
INTEGRATED LED MODULE	1 x LED/17W/120-277V LED

Technical Information

APERTURE SHAPE	Round
HOUSING HEIGHT	5"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	18°
COLOR RENDERING	90 CRI
LAMP COLOR	2700K
LUMENS/WATT	86.82
LUMINOUS FLUX	1476 lumens



Shown in black



CLICK TO VIEW PRODUCT

Notes: