



BRAND

Visual Comfort Architectural

DESCRIPTION

The 3 Inch Square 90CRI LED Adjustable Downlight Non-IC Remodel Housing for use with square flanged trims. Features precision aiming mechanism with a 0-40 degree tilt, 361 degree rotation, and high-low lamp positioning. Includes 12 or 17 watt LED module in 2700K, 3000K or 3500K color temperature options or Warm Dim (3000K-1800K) and 10, 18, 25, 40 or 60 degree beam angle options. 3 7/8 inch cut out. Suitable for damp locations. Suitable for wet locations with shower trim option. Includes a 120-277V Universal driver dimmable with standard reverse-phase, forward-phase, TRIAC, and 0-10V dimming. Note: A complete fixture requires a housing and trim, sold separately. .Note: 10 degree beam angle not available for Warm Dim option.





Shown in: Black

TRIM COLOR	N/A
BODY FINISH	Black
WATTAGE	17W
DIMMER	Low Voltage Electronic
DIMENSIONS	3.8"W x 5.8"H
INTEGRATED LED MODULE	
LAMP	1 x LED/17W/120-277V LED


Technical Information

LUMINOUS FLUX	1450 lumens
LUMENS/WATT	85.29
LAMP COLOR	2700K
COLOR RENDERING	90 CRI
BEAM ANGLE	25°
LAMP LIFE	50000 hours
FUNCTION	Adjustable Accent
CEILING TYPE	Drywall with Trim
HOUSING TYPE	Remodel NON IC

SPEC #	ELE361254
--------	-----------



DRIVER



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE