



BRAND Visual Comfort Architectural


DESCRIPTION

3 Inch Square 90CRI Fixed Downlight Non-IC Remodel Housing designed for use with square flanged trims. Features high-low lamp positioning. Includes LED module in 2700K, 3000K and 3500K color temperature options in low output (12 watt) or high output (17 watt) and 10, 18, 25, 40 or 60 degree beam angle, or Warm Dim (3000K-1800K) and 18, 25, 40 or 60 degree beam angle. 3 7/8 inch cut out. Suitable for damp locations. Suitable for wet locations with shower trim option. Includes a 120-277V Universal driver dimmable with standard reverse-phase, forward-phase, TRIAC, and 0-10V dimming. Note: A complete fixture requires a housing and trim, sold separately. Note: Warm Dim option is not available with 10 degree beam angle.



Shown in: Black

TRIM COLOR	N/A
BODY FINISH	Black
WATTAGE	17W
DIMMER	Low Voltage Electronic
DIMENSIONS	3.8"W x 5"H
INTEGRATED LED MODULE	
LAMP	1 x LED/17W/120-277V LED
Technical Information	
LUMINOUS FLUX	1450 lumens
LUMENS/WATT	85.29
LAMP COLOR	2700K
COLOR RENDERING	90 CRI
BEAM ANGLE	25°
LAMP LIFE	50000 hours
CEILING TYPE	Drywall with Trim
HOUSING TYPE	Remodel NON IC
HOUSING HEIGHT	5"
SPEC #	ELE361255



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE