

Lightology

lightology.com
866-954-4489
01-11-26

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **EDG362721**
Approved On: _____ Approved By: _____

RGB 2X100W 24V LED Power Supply with DMX Driver

By PureEdge Lighting



Description

The PSB-2X100W-24VDC-RGB Class 2 LED Power Supply accepts input voltage in a range of 120-277 volts AC and outputs 24 volts DC power up to 2X100 watts. The integrated RGB driver receives signals from CDP, CTP, CDMX1-RGBW or CDMX1-2XK to control RGB color mixing and light intensity. Features short circuit and overload protection. For indoor applications only. To avoid overheating the power supply, install it in a ventilated remote location where air flows.


Maintain proper spacing among power supplies when multiple power supplies are installed in the same remote location. Power Input: 120-277VAC, 50/60Hz. Power Output: Class 2, 24VDC, 2X4.16A, 2X100 watts maximum. Compatible Controllers: Touch Screen Controller with Power Supply (CTP), Color Dial Controller with Power Supply (CDP), DMX 1-Zone RGBW Touch Controller (CDMX1-RGBW), or Tunable White Touch Controller (CDMX1-2XK), sold separately. ETL listed. 14 inch width x 10 inch depth x 3 inch height.

Specifications


COLOR	N/A
BODY FINISH	White
WATTAGE	200W
DIMMER	Dimmable
DIMENSIONS	14"W x 3"H x 10"D
BULB NOT INCLUDED	N/A



Shown in white



Top View



Side View



CLICK TO VIEW PRODUCT

Notes: