



lightology.com
866-954-4489
08-04-25

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **EDG362722**

Approved On: _____ Approved By: _____

RGB 3X100W 24V LED Power Supply with DMX Driver

By PureEdge Lighting



Description


The PSB-3X100W-24VDC-RGB Class 2 LED Power Supply accepts input voltage in a range of 120-277 volts AC and outputs 24 volts DC power up to 3X100 watts. The integrated RGB driver receives signals from CDP, CTP, CDMX1-RGBW or CDMX1-2XK to control RGB color mixing and light intensity. Features short circuit and overload protection. For indoor applications only. To avoid overheating the power supply, install it in a ventilated remote location where air flows. Maintain proper spacing among power supplies when multiple power supplies are installed in the same remote location. Power Input: 120-277VAC, 50/60Hz. Power Output: Class 2, 24VDC, 3X4.16A, 3X100 watts maximum. Compatible Controllers: Touch Screen Controller with Power Supply (CTP), Color Dial Controller with Power Supply (CDP), DMX 1-Zone RGBW Touch Controller (CDMX1-RGBW), or Tunable White Touch Controller (CDMX1-2XK), sold separately. ETL listed. 17 inch width x 13 inch depth x 3 inch height.

Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	300W
DIMMER	Dimmable
DIMENSIONS	17"W x 13"H x 3"D
BULB NOT INCLUDED	N/A



Shown in white



CLICK TO VIEW PRODUCT

Notes: