

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: ELE364723	1 //(0.10 /// // // // // // // // // // // // /
Approved On:	Approved By:

Element 3IN RD Flanged Adjustable New Construction Housing By Visual Comfort Architectural









Description

3 Inch Round 90CRI Adjustable Downlight Non-IC, IC or Chicago Plenum New Construction Housing for round flanged trims. This small aperture LED downlight is fully adjustable and the design allows the LED to be positioned closer to the aperture for maximum light output and efficiency, or higher to minimize glare on the trim. Additional adjustability allows for tool-free hot aiming and locking, including 0 to 40 degree tilt and 361 degree rotation to eliminate dead spots. Includes 12 or 17 watt LED modules and a choice of 2700K, 3000K or 3500K color temperature and 10, 15, 25, 40 or 60 degree beam angle. 3 7/8 inch ceiling opening. Suitable for damp locations. Suitable for wet locations with shower trim option. Includes a 120-277V Universal driver dimmable with standard reverse-phase, forward-phase, TRIAC, and 0-10V dimming. Note: A complete fixture requires a housing and trim, sold separately. Note: Warm Dim option is not available with 10 degree beam angle.

Specifications

BODT FINIST	Jai
WATTAGE	7W
DIMMER Low Voltage Electron	nic
DIMENSIONS	5"D
INTEGRATED LED MODULE	ED
Technical Information	
APERTURE SHAPE Rou	nd
HOUSING HEIGHT	4"
HOUSING TYPE Chicago plenum approv	ed
CEILING TYPE	im
FUNCTION	ent
BEAM ANGLE	18°
COLOR RENDERING	CRI
LAMP COLOR	ΟK
LUMENS/WATT	.59

 COLOR
 N/A

 BODY FINISH
 Black Powder Coat



Shown in black powder coat





CLICK TO VIEW PRODUCT

Notes:		