

Lightology

lightology.com
866-954-4489
11-07-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **ELE364991**
Approved On: _____ Approved By: _____

Element 3IN SQ Flangeless Downlight New Construction Housing By Visual Comfort Architectural



Description

3 Inch Square 90CRI Flangeless Fixed Downlight Non-IC Airtight, IC Airtight, or Chicago Plenum New Construction Housing for square flangeless trims. Small aperture LED downlight with architectural appearance. Includes a 12 or 17 watt LED module in three color temperature options and Warm Dim LED (3000K-1800K). Offered with a 10, 18, 25, 40 or 60 degree beam angle. 3 7/8 inch ceiling opening. Suitable for damp locations. Suitable for wet locations with shower trim option. Includes a 120-277V Universal driver dimmable with standard reverse-phase, forward-phase, TRIAC, and 0-10V dimming. Note: A complete fixture requires a housing and trim, sold separately. Note: Warm Dim option is not available with 10 degree beam angle.

Specifications

COLOR N/A
BODY FINISH Black
WATTAGE 17W
DIMMER Low Voltage Electronic
DIMENSIONS 12.5"L x 9.5"W x 4"H
INTEGRATED LED MODULE 1 x LED/17W/120-277V LED

Technical Information


APERTURE SHAPE Square
HOUSING HEIGHT 4"
HOUSING TYPE Chicago plenum approved
CEILING TYPE Drywall Trimless/Flush
FUNCTION Downlight
BEAM ANGLE 40°
COLOR RENDERING 90 CRI
LAMP COLOR 2700K
LUMENS/WATT 70.59
LUMINOUS FLUX 1200 lumens



IC AIR*

IC Airtight*

Shown in black



CLICK TO VIEW PRODUCT

Notes: