



BRAND

Contrast Lighting

DESCRIPTION

Modul Aim 1-Light Electronic Low Voltage Dim IC New Construction Assembled Housing with CrispWhite Technology features a powder coated 22 gauge galvanized steel housing to fit in ceilings up to 1 inch thick. Available in Matte White or Matte Black. IC rated for direct contact with insulation. Swivels 359 degrees and tilts 40 degrees with a one screw locking device to lock both axis in position. Includes 20 watts LED with 3000K Warm White color temperature, 90+ CRI, 1195 lumens. Features Lumileds Luxeon CoB 1205 LED engine with CrispWhite Technology, delivering the warm saturated colors of high 90+ CRI solutions while creating the natural crisp whiteness required for merchandising. 50,000 hour average lamp life. Optical reflectors available in 15 degree spot, 19 degree medium spot, 32 degree narrow flood and 45 degree wide flood. UL listed for damp locations. Energy Star certified. 5 year warranty on LED module and driver. 6.25 inch x 6.25 inch ceiling cut-out. 14.62 inch length x 10 width x 6 inch height housing. Available in a with trim option, available in three finishes, or a trimless option requiring a mesh plate. Optional Mask accessory available to conceal interior components to give a more finished look. Dimmable with an electronic low voltage dimmer per attached manufacturer dimmer compatibility recommendations. Required trim, mesh plate for trimless, optional mask and dimmer control, sold separately.



TRIM COLOR	N/A
BODY FINISH	Matte Black
WATTAGE	20W
DIMMER	Low Voltage Electronic
DIMENSIONS	14.62"L x 10"W x 6"H
INTEGRATED LED MODULE	
LAMP	1 x LED/20W/120V LED

Technical Information

LUMINOUS FLUX	1195 lumens
LUMENS/WATT	59.75
LAMP COLOR	3000K
COLOR RENDERING	90 CRI
BEAM ANGLE	19°
LAMP LIFE	50000 hours
HOUSING TYPE	New construction IC
HOUSING HEIGHT	6"
APERTURE SHAPE	Round
SPEC #	CLT371793

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE