



### BRAND

Contrast Lighting

### DESCRIPTION

Modul Aim 1-Light Electronic Low Voltage Dim Non-IC New Construction Assembled Housing with 19 Degree Beam Angle features a powder coated 22 gauge galvanized steel housing to fit in ceilings up to 1 inch thick. Available in Matte White or Matte Black. Non-IC rating requires no contact with insulation and at least 3 inch clearance between housing and insulation. Swivels 359 degrees and tilts 40 degrees with a one screw locking device to lock both axis in position. Includes 20 watts LED with choice of 2700K Very Warm White, 3000K Warm White, 3500K Neutral White or 4000K Cool White color temperature, 90+ CRI. Features Lumileds Luxeon CoB 1205 LED engine, delivering approximately 63 lumens per watt with a lumen maintenance greater than 70 percent after 50,000 hours of operation. Optical reflectors available in 15 degree spot, 19 degree medium spot, 32 degree narrow flood and 45 degree wide flood. UL listed for damp locations. Energy Star certified. 5 year warranty on LED module and driver. 6.25 inch x 6.25 inch ceiling cut-out. 10.5 inch length x 7.18 inch width x 7.56 inch height housing. Available in a with trim option, available in three finishes, or a trimless option requiring a mesh plate. Optional Mask accessory available to conceal interior components to give a more finished look. Dimmable with an electronic low voltage dimmer per attached manufacturer dimmer compatibility recommendations. Required trim, trimless mesh plate, optional mask and dimmer control, sold separately.



TRIM COLOR	N/A
BODY FINISH	Matte White
WATTAGE	20W
DIMMER	Low Voltage Electronic
DIMENSIONS	10.5"L x 7.18"W x 7.56"H
INTEGRATED LED MODULE	
LAMP	1 x LED/20W/120V LED

#### Technical Information

LUMINOUS FLUX	1194 lumens
LUMENS/WATT	59.70
LAMP COLOR	2700K
COLOR RENDERING	90 CRI
BEAM ANGLE	19°
LAMP LIFE	50000 hours
FUNCTION	Adjustable Accent
HOUSING TYPE	New Construction NON IC
HOUSING HEIGHT	8"
SPEC #	CLT372217

COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE