



BRAND

Contrast Lighting

DESCRIPTION

Modul Aim 1-Light Electronic Low Voltage Dim Non-IC Remodel Assembled Housing with 15, 19, 32 or 45 Degree Beam Angle and CrispWhite Technology features a powder coated 22 gauge galvanized steel housing to fit in ceilings up to 2 inch thick. Available in Matte White or Matte Black. Non-IC rating requires no contact with insulation and at least 3 inch clearance between housing and insulation. Swivels 359 degrees and tilts 40 degrees with a one screw locking device to lock both axis in position. Includes 20 watts LED with 3000K Warm White color temperature, 90+ CRI, 1195 lumens. Features Lumileds Luxeon CoB 1205 LED engine with CrispWhite Technology, delivering the warm saturated colors of high 90+ CRI solutions while creating the natural crisp whiteness required for merchandising. 50,000 hour average lamp life. Optical reflectors available in 15 degree spot, 19 degree medium spot, 32 degree narrow flood and 45 degree wide flood. UL listed for damp locations. Energy Star certified. 5 year warranty on LED module and driver. 6.25 inch x 6.25 inch ceiling cut-out. 7.18 inch length x 6 width x 7.56 inch height housing. Available in a with trim option, available in three finishes, or a trimless option requiring a mesh plate. Optional Mask accessory available to conceal interior components to give a more finished look. Dimmable with an electronic low voltage dimmer-see attached Performance 1 manufacturer dimmer compatibility recommendations. Required trim, mesh plate for trimless, optional mask and dimmer control, sold separately.



| | |
|-----------------------|------------------------|
| TRIM COLOR | N/A |
| BODY FINISH | Matte Black |
| WATTAGE | 20W |
| DIMMER | Low Voltage Electronic |
| DIMENSIONS | 7.18"L x 6"W x 7.56"H |
| INTEGRATED LED MODULE | |
| LAMP | 1 x LED/20W/120V LED |

Technical Information

| | |
|-----------------|-------------------|
| LUMINOUS FLUX | 1195 lumens |
| LUMENS/WATT | 59.75 |
| LAMP COLOR | 3000K |
| COLOR RENDERING | 90 CRI |
| BEAM ANGLE | 19° |
| LAMP LIFE | 50000 hours |
| FUNCTION | Adjustable Accent |
| HOUSING TYPE | Remodel NON IC |
| HOUSING HEIGHT | 8" |
| SPEC # | CLT373389 |

COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE