

lightology.com 866-954-4489 12-13-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG377587	
Approved On:	Approved By:

Verge Ceiling Static White Drywall Plaster-In System 24V By PureEdge Lighting








Description

Verge Ceiling features an innovative design that recesses within 5/8 inch drywall without joist modification. Available in 1 foot increments (sold in 5 foot increments) up to 40 feet (2 Watt), 20 feet (5 Watt), and 12 feet (7 Watt) and is field-cuttable. The plaster-in aluminum extrusion features a 4 inch paintable backer plate and highlights ceiling perimeters while emitting smooth and continuous ambient illumination.Included Components: Junction Box, Adjustable Mounting Bars, Backer Plate, Verge Ceiling Channel(s), Drywall Screws, LED Soft Strip and Lens(es). System requires a remote Universal (UNI) power supply. A VG-1RE-JBOX rough-in junction box is available to rough-in electrical before drywall installation (included and sold separately). Product is built to order. Note: Required power supply, dimmer control, and optional mounting accessories sold separately. MAXIMUM LENGTHS BEFORE RE-FEEDING:2WDC, 2.5 watts per foot - 40 Feet5WDC, 4.4 watts per foot - 20 Feet7WDC, 7.5 watts per foot - 12 Feet

Specifications COLOR

WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE
Technical Information
LAMP LIFE
COLOR RENDERING
LAMP COLOR
LUMENS/WATT
LUMINOUS FLUX





Notes: