Lightology

lightology.com
866-954-4489
10-29-26

Project:

Company:

Location: Fixture Type:

SPEC #: **EDG395811**

Approved On: Approved By:

Twist Strip 3.3W Commercial Grade 24V


By PureEdge Lighting

Description

TS3C commercial-grade 24 volt Twist Strip uses high CRI LEDs for superior color rendering and bends up to 90 degrees for installations requiring horizontal bends. The .4 inch wide flexible copper strip, with an optically clear protective coating, is sold in 10 and 20 foot lengths and can be cut every 4 inches. Includes 3.3 watts per foot with 2700K or 3000K color temperature. System can be powered with an electronic low voltage or 0-10V power supply. ELV power supply dimmable with: Legrand, Adorne ADTP703TU, Lutron Diva, DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600, or Lutron Radio Ra 2. 0-10V power supply dimmable with: Philips Sunrise SR1200ZTUNB. Self-adhering Twist Strip mounts to most smooth finished surfaces with industrial strength 3M tape provided on back of strip. Some unfinished surfaces may require screw in mounting clips, sold separately. Snap & Light power connector is required, sold separately. Compatible with solderless Snap & Light connectors for making turns and custom configurations. Suitable for damp locations. ETL listed. 5 year warranty. Required power supply and Snap & Light power connector, dimmer control and optional mounting accessories sold separately. Product is built to order.



Shown in clear



Specifications

COLOR	N/A
BODY FINISH	Clear
WATTAGE	33W
DIMMER	Dimmable
DIMENSIONS	120"L x 0.4"W
INTEGRATED LED MODULE	1 x LED/33W/24V LED

Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	95 CRI
LAMP COLOR	2700K
LUMENS/WATT	65.76
LUMINOUS FLUX	2170 lumens

CLICK TO VIEW PRODUCT

Notes: