

Lightology

lightology.com
866-954-4489
08-26-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **HAD400558**
Approved On: _____ Approved By: _____

IUL516 LED Composite Inground Uplight

By Hadco by Signify



Description

IUL516 LED Composite Inground Uplight is fabricated from one piece injection molded high performance polymer composite. Composite is textured, pressure formed, molded in color in Bronze. Lens ring is a single piece injection molded high performance polymer with gasketed lens and twist off operation for ease of maintenance. Clear convex, tempered glass furnished with silicone O-ring for watertight seal. Includes one 7 watt 12 volt GU5.3 MR16 LED lamp with 25 degree beam spread, 3000K color temperature, 460 lumens. 25,000 hour average lamp life. Pre-wired with 3 foot pigtail of 18-2 AWG wire. Includes low voltage quick connector LVC3 for easy hook up to the low voltage supply cable, sold separately. 4.1 inch diameter x 4.4 inch height. ETL listed for wet locations. 5 year limited warranty. Requires remote transformer, sold separately.

Specifications


COLOR	N/A
BODY FINISH	Bronze
WATTAGE	7W
DIMMER	Dimmable
DIMENSIONS	4.1"W x 4.4"H
BULB INCLUDED	1 x MR16/GU5.3 (bipin)/7W/12V LED

Technical Information

LAMP LIFE	25000 hours
BEAM ANGLE	25°
LAMP COLOR	3000K
LUMENS/WATT	65.71
LUMINOUS FLUX	460 lumens



Shown in bronze



CLICK TO VIEW PRODUCT

Notes: