

lightology.com 866-954-4489 10-16-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: HAD400558	
Approved On:	Approved By:

IUL516 LED Composite Inground Uplight By Hadco by Signify





Description

IUL516 LED Composite Inground Uplight is fabricated from one piece injection molded high performance polymer composite. Composite is textured, pressure formed, molded in color in Bronze. Lens ring is a single piece injection molded high performance polymer with gasketed lens and twist off operation for ease of maintenance. Clear convex, tempered glass furnished with silicone O-ring for watertight seal. Includes one 7 watt 12 volt GU5.3 MR16 LED lamp with 25 degree beam spread, 3000K color temperature, 460 lumens. 25,000 hour average lamp life. Pre-wired with 3 foot pigtail of 18-2 AWG wire. Includes low voltage quick connector LVC3 for easy hook up to the low voltage supply cable, sold separately. 4.1 inch diameter x 4.4 inch height. ETL listed for wet locations. 5 year limited warranty. Requires remote transformer, sold separately.

Specifications COLOR

WATTAGE
DIMMER Dimmable
DIMENSIONS
BULB INCLUDED
Technical Information
LAMP LIFE
BEAM ANGLE
LAMP COLOR
LUMENS/WATT
LUMINOUS FLUX



Shown in bronze







CLICK TO VIEW PRODUCT

Notes:		