

Lightology

lightology.com
866-954-4489
04-22-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG429596**
 Approved On: _____ Approved By: _____

Glide Glass Downlight Suspension w/ Center Feed Power

By PureEdge Lighting



Description

Glide Glass Center Feed Downlight Suspension features a diffused white lens with 100 degree beam spread. Glass available in Black, White or Mirror with optional black or white louvers. Channel lengths sold in 12 inch increments from 36 to 120 inches with 5, 7 or 10 watt options. Available in a variety of color temperature options. Includes rectangle canopy with 120V input/24VDC output Universal (UNI) LED power supply (dimmable with an electronic low voltage (ELV), 0-10V, or Triac (magnetic dimmer). Note: Product is built to order.

Specifications


COLOR No Louver
 BODY FINISH Mirror Glass
 WATTAGE 15W
 DIMMER Low Voltage Electronic
 DIMENSIONS 36"L x 1.74"W x 2.5"H
 INTEGRATED LED MODULE 3 x LED/5W/120V LED

Technical Information

LAMP LIFE 50000 hours
 COLOR RENDERING 92 CRI
 LAMP COLOR 2700K
 LUMENS/WATT 162.00
 LUMINOUS FLUX 810 lumens



Shown in mirror glass / no louver



CLICK TO VIEW PRODUCT

Notes: