

Lightology

lightology.com
866-954-4489
04-22-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **ELE449337**

Approved On: _____ Approved By: _____

Element 4IN SQ Flangeless Fixed New Construction Housing By Visual Comfort Architectural



Description

The 4 Inch Square Flangeless Fixed Downlight Non-IC Airtight or IC Airtight New Construction Housing is constructed of heavy gauge cold rolled steel with a durable Black powder coat finish. This specification grade housing features an integral low output 17 watt, high output 29 watt, or max output 35 watt LED module available with choice of 2700K, 3000K or 3500K color temperature, or Warm Dim 3000K-1800K. Available in a 10 degree (17 watt only), 18 degree, 25 degree, 40 degree, or 60 degree beam angle option. High-low positioning, 45 degree collar rotation. 4.50 inch ceiling cutout. Note: A complete fixture requires a housing and trim, sold separately. Not all options are available. Note: 10 degree beam angle available on low output 17 watt 2700K, 3000K and 3500K color temperature options only. Warm Dim not available on 35 watt option.

Specifications

REFLECTOR/BAFFLE COLOR N/A
BODY FINISH Black
WATTAGE 29W
DIMMER Low Voltage Electronic
DIMENSIONS 14.5"L x 11.5"W x 5.3"H
INTEGRATED LED MODULE 1 x LED/29W/120V LED

Technical Information

APERTURE SIZE 4.000"
APERTURE SHAPE Square
HOUSING HEIGHT 6"
HOUSING TYPE New construction NON IC Airtight
CEILING TYPE Drywall Trimless/Flush
FUNCTION Downlight
BEAM ANGLE 18°
COLOR RENDERING 90 CRI
LAMP COLOR 2700K
LUMENS/WATT 71.03
LUMINOUS FLUX 2060 lumens



Shown in black



CLICK TO VIEW PRODUCT

Notes: