



BRAND

Visual Comfort Architectural

DESCRIPTION

The 4 Inch Square Flangeless Fixed Downlight Non-IC Airtight or IC Airtight New Construction Housing is constructed of heavy gauge cold rolled steel with a durable Black powder coat finish. This specification grade housing features an integral low output 17 watt, high output 29 watt, or max output 35 watt LED module available with choice of 2700K, 3000K or 3500K color temperature, or Warm Dim 3000K-1800K. Available in a 10 degree (17 watt only), 18 degree, 25 degree, 40 degree, or 60 degree beam angle option. High-low positioning, 45 degree collar rotation. 4.50 inch ceiling cutout. Note: A complete fixture requires a housing and trim, sold separately. Not all options are available. Note: 10 degree beam angle available on low output 17 watt 2700K, 3000K and 3500K color temperature options only. Warm Dim not available on 35 watt option.



Shown in: Black

TRIM COLOR	N/A
BODY FINISH	Black
WATTAGE	29W
DIMMER	Low Voltage Electronic
DIMENSIONS	14.5"L x 11.5"W x 5.3"H
INTEGRATED LED MODULE	
LAMP	1 x LED/120V LED

Technical Information

LUMINOUS FLUX	2060 lumens
LUMENS/WATT	71.03
LAMP COLOR	2700K
COLOR RENDERING	90 CRI
BEAM ANGLE	40°
FUNCTION	Downlight
CEILING TYPE	Drywall Trimless/Flush
HOUSING TYPE	New construction NON IC Airtight
HOUSING HEIGHT	6"
SPEC #	ELE449339

COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE