

Lightology

lightology.com
866-954-4489
12-08-25

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **JUN472532**

Approved On: _____ Approved By: _____

6RLS Gen 2 LED Basics Series Surface Mount 1000 Lumen

By Juno Lighting



Description


6RLS Gen 2 Basics Series Surface Mount is a sleek, ultra-low profile energy efficient LED fixture for junction box or recessed housing installation. Installs directly onto industry standard junction boxes and round mud rings. When used with accessory retrofit kit, fixture can be installed into 5 or 6 inch IC or non-IC recessed housings with an inside diameter between 5 and 7 inches and a minimum height of 4 inches. Decorative beveled aluminum trim frame with White finish. Diffusing dome lens. Includes 14.5 watts LED with choice of 2700K or 3000K color temperature, 90CRI, 1000 lumens. Replaces traditional 75 watt incandescent fixture performance. Dimmable with most standard incandescent, magnetic and electronic low voltage dimmers. 50,000 hour average lamp life. UL listed. Suitable for wet locations. Energy Star. Title 24 compliant. 5 year warranty.

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White
WATTAGE	14.5W
DIMMER	Dimmable
DIMENSIONS	7.38"W x 1.25"H
INTEGRATED LED MODULE	1 x LED/14.5W/120V LED

Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	90 CRI
LAMP COLOR	3000K
LUMENS/WATT	68.97
LUMINOUS FLUX	1000 lumens



Notes:

--